

0	<b>,</b>	•				
Report No. : TCT220216C018		Date : Feb. 21, 202	22	Page No.:	1 of 8	
Applicant:	ShenZhen Jieshib	henZhen Jieshibo Technology CO.,Ltd				
Address:	3Building, Xianyux	king Industrial Park, I	Fuhe Road Go	nghe Comm	unity,	
	Shajing Street, Ba	oan District, Shenzhe	en City, China			
The following sample w	as submitted and id	dentified by/on behal	f of the client a	as:		
Sample Name:	VPEN Disposable	e Vape Pen				
Model No.:	JY1305					
Flavour:	Vanilla 🎸					
Power level in testing:	Voltage/Wattage	of tested sample is un	-adjustable			
Adjustable air inlet or not	: No					
Trade Mark:						
Sample Received Date:	2022.02.16					
Testing Period:	2022.02.16—202	2.02.21				
Test Method:	Please refer to th	e following page(s).				
Test Result(s):	Please refer to th	e following page(s).				

t Items	Test Requested
Carbonyl Compounds: Formaldehyde, Acetaldehyde, Acrolein, Crotonaldehyde	
Metals: Aluminum, Chromium, Iron, Nickel, Tin, Lead, Cadmium, Arsenic, Antimony	Emission testing
Nicotine consistency	according to
Diacetyl and Pentane 2,3 dione	Article 20 of
Ethylene Glycol and Diethylene Glycol	Tobacco Product
Specific Nitrosamines: N-nitrosonornicotine(NNN),	Directive
4-(N-methylnitrosamino)-1-(3-pyridyl)-1-butanone(NNK)	(2014/40/EU)
VOC substances: Toluene, Benzene, 1,3-Butadiene, Isoprene	
	Carbonyl Compounds: Formaldehyde, Acetaldehyde, Acrolein, Crotonaldehyde Metals: Aluminum, Chromium, Iron, Nickel, Tin, Lead, Cadmium, Arsenic, Antimony Nicotine consistency Diacetyl and Pentane 2,3 dione Ethylene Glycol and Diethylene Glycol Specific Nitrosamines: N-nitrosonornicotine(NNN), 4-(N-methylnitrosamino)-1-(3-pyridyl)-1-butanone(NNK)





Report No. : TCT220216C018

Date : Feb. 21, 2022

Page No.: 2 of 8

#### **Test Results:**

Test Condition for test items except Nicotine consistency test:

With reference to the CORESTA RECOMMENDED METHOD Nº 81 method parameter, Afnor standardization XP D90-300-3, International Standard ISO 20768:2018 and PD CEN/TR 17236:2018, a smoke machine was used to collect the vapor.

Puff Duration	3.0s±0.1s		
Puff Volume		55mL±0.3mL	
Puff Frequency		30s±0.5s	Ň
Puff of Each Group		20	J
Group Interval Time	300s±120s		
Maximum Flow		18.5mL/s±1.0mL/s	
Pressure Drop		< 50hPa	
Group		5	
Total Number of Puff		100	3
Total Duration of Vaporization	S)	300s	Ż
	Puff Volume Puff Frequency Puff of Each Group Group Interval Time Maximum Flow Pressure Drop Group Total Number of Puff	Puff Volume   Puff Frequency   Puff of Each Group   Group Interval Time   Maximum Flow   Pressure Drop   Group   Total Number of Puff	Puff Volume55mL±0.3mLPuff Frequency30s±0.5sPuff of Each Group20Group Interval Time300s±120sMaximum Flow18.5mL/s±1.0mL/sPressure Drop< 50hPa

The temperature and relative humidity of the test atmosphere during machine preparation and testing were kept within the following limits: temperature  $\pm 2^{\circ}$ C, relative humidity  $\pm 5\%$ 

#### **Specimen Description:**





Report No. : TCT220216C018

Date : Feb. 21, 2022

Page No.: 3 of 8

### 1. Carbonyl Compounds Content(s)

Test method: According to XP D90-300-3:2016, the aerosol generated by the e-cigarette is absorbed by the impactor containing 40mL acidified solution of 2,4-dinitrophenylhydrazine (DNPH) in acetonitrile. The solution was filtered and analyzed by reverse phase high - performance liquid chromatography and determined using a UV detector.

Test Item	CAS No.	Unit	MDL	Content(s)	
Test nem	CAS NO.	Unit	NDL	No.1	
Formaldehyde	50-00-0	µg/100puffs	0.5	ND	6
Acetaldehyde	75-07-0	µg/100puffs	0.5	0.920	C
Acrolein	107-02-8	µg/100puffs	0.5	ND	
Crotonaldehyde	4170-30-3	µg/100puffs	0.5	ND	

- ND = Not Detected (less than MDL)
- MDL = Method Detection Limit



Report No. : TCT220216C018

Date : Feb. 21, 2022

Page No.: 4 of 8

### 2. Metals Content(s)

Test method: According to Afnor XP D90-300-3:2016 Annex A.6, wipe the clamp with isopropyl alcohol. Let stand for a minute. 20 ml of nitric acid was added to the impactor, and placed in series with the Cambridge filter to absorb the aerosol. The Cambridge filter was removed and placed in nitric acid, shaken at 210 rpm for 30 min, and the solution was filtered and analyzed by ICP-MS.

Test Item	CAS No.	Unit	MDL	Content(s)
Test tiem	CA5 NO.	Unit	MDL	No.1
Aluminum(Al)	7429-90-5	µg/100puffs	0.01	ND
Chromium(Cr)	7440-47-3	µg/100puffs	0.01	ND
Iron(Fe)	7439-89-6	µg/100puffs	0.01	ND
Nickel(Ni)	7440-02-0	µg/100puffs	0.01	0.834
Tin(Sn)	7440-31-5	µg/100puffs	0.01	ND
Lead(Pb)	7439-92-1	µg/100puffs	0.01	ND
Cadmium(Cd)	7440-43-9	µg/100puffs	0.01	ND
Arsenic(As)	7440-38-2	µg/100puffs	0.01	ND
Antimony(Sb)	7440-36-0	µg/100puffs	0.01	ND

- ND = Not Detected (less than MDL)
- MDL = Method Detection Limit



Report No. : TCT220216C018

Date : Feb. 21, 2022

Page No.: 5 of 8

### 3. Nicotine Consistency Test

Test Condition: With reference to the CORESTA RECOMMENDED METHOD Nº 81 method parameter and Afnor standardization XP D90-300-3, a smoke machine was used to collect the vapor.

Puff Duration	3.0s±0.1s		
Puff Volume	55mL±0.3mL		
Puff of Each Group	20		
Maximum Flow	18.5mL/s±1.0mL/s		
Pressure Drop	< 50hPa		

The temperature and relative humidity of the test atmosphere during machine preparation and testing were kept within the following limits: temperature  $\pm 2^{\circ}$ , relative humidity  $\pm 5\%$ 

Test method: According to Afnor XP D90-300-3:2016 Annex A.3, wipe the clamp with isopropyl alcohol. Let stand for a minute. The aerosol generated by the e-cigarette is absorbed by the Cambridge filter. Remove the Cambridge filter and place it into a centrifuge tube, add 20 mL of Isopropyl alcohol and 0.2ml Internal standard stock solution. Shaken at 210 rpm for 30 min, and the solution was filtered and analyzed by GC-FID.

Nicotine(CAS No.:54-11-5) Contents(mg/20Puffs)							Total
Sample No.	Group 1*	Group 2	Group 3*	Group 4	Group 5*	AVG	(mg/100puffs)
No.1	2.19	2.16	2.15	2.18	2.19	2.17	10.9
Deviation (%)	0.7	-	1.1	-	0.7	-	-

Note: - mg = milligram

- ND = Not Detected (less than MDL)
- MDL = Method Detection Limit = 0.05mg/20Puffs
- 1group = 20puffs
- \* Values used for determination of consistency of nicotine emission
- Under the conditions of the test and with reference to AFNOR XP D90-300-3, the electronic cigarette delivers a dose of nicotine at consistent levels.



Report No. : TCT220216C018

Date : Feb. 21, 2022

Page No.: 6 of 8

### 4. Diacetyl and Pentane 2,3 dione Content(s)

Test method: According to Afnor XP D90-300-3:2016 Annex A.4, the aerosol generated by the e-cigarette is absorbed by the impactor containing 20mL methanol. The solution was filtered and analyzed by GC-MS.

Test Item			MDL	Content(s)
Test Item	CAS No. UI	Unit	MDL	No.1
Diacetyl	431-03-8	µg/100puffs	5.0	ND
Pentane 2,3 dione	600-14-6	µg/100puffs	5.0	ND ND

#### Note: - $\mu g = Microgram$

- ND = Not Detected (less than MDL)
- MDL = Method Detection Limit

## 5. Ethylene Glycol and Diethylene Glycol Content(s)

Test method: According to SOP-CL-090, wipe the clamp with isopropyl alcohol. Let stand for a minute. 20 ml of methanol was added to the impactor and placed in series with the Cambridge filter to absorb the aerosol. The Cambridge filter was removed and placed in methanol, shaken at 210 rpm for 30 min, and the solution was filtered and analyzed by GC-FID.

				Content(s)	S)
Test Item	CAS No.	Unit	MDL	No.1	
Ethylene Glycol	107-21-1	µg/100puffs	1.0	ND	
Diethylene Glycol	111-46-6	µg/100puffs	1.0	ND G	

- ND = Not Detected (less than MDL)
- MDL = Method Detection Limit



Report No. : TCT220216C018

Date : Feb. 21, 2022

Page No.: 7 of 8

### 6. Specific Nitrosamines Content(s)

Test method: According to CORESTA Recommended Method No. 75(2019), wipe the clamp with isopropyl alcohol. Let stand for a minute. The aerosol generated by the e-cigarette is absorbed by Cambridge filter, and the Cambridge filter was removed and placed in an Erlenmeyer flask, added to 20 mL of 100 mM ammonium acetate solution, shaken at 210 rpm for 60 min, filtered and analyzed by LC-MS/MS.

Test Item	CAS No.	Unit	MDL	Content(s)	
iest item	CAS NO.	Offic	MDL	No.1	
N-nitrosonornicotine(NNN)	80508-23-2	µg/100puffs	0.2	ND	
4-(N-methylnitrosamino)-1-(	64004 04 4	ug/100puffa	0.0		S
3-pyridyl)-1-butanone(NNK)	64091-91-4	µg/100puffs	0.2	ND	

### Note: - $\mu g = Microgram$

- ND = Not Detected (less than MDL)
- MDL = Method Detection Limit

### 7. VOC substances content(s)

Test method: According to CORESTA Recommended Method No.70 (2019), wipe the clamp with isopropyl alcohol. Let stand for a minute. 20 ml of methanol was added to the impactor and placed in series with the Cambridge filter to absorb the aerosol. The Cambridge filter was removed and placed in methanol, shaken at 210 rpm for 30 min, and the solution was filtered and analyzed by GC-MS.

Test Item CAS No.				Content(s)	
		Unit	MDL	No.1	
Toluene	108-88-3	µg/100puffs	2.0	ND	
Benzene	71-43-2	µg/100puffs	2.0	ND	
1,3-Butadiene	106-99-0	µg/100puffs	2.0	ND	2
Isoprene	78-79-5	µg/100puffs	2.0	ND ND	)

- ND = Not Detected (less than MDL)
- MDL = Method Detection Limit



Report No. : TCT220216C018

Date : Feb. 21, 2022

Page No.: 8 of 8



Remark: This report is considered invalidated without the Special Seal for Inspection of the TCT. This report shall not be altered, increased or deleted. The results shown in this test report refer only to the sample(s) tested. Without written approval of TCT, this test report shall not be copied except in full and published as advertisement.

